

DIGITAL INSULATION TESTER DIT99A

APPLICATION: This is a high Quality Multirange Insulation Tester with big Backlight display.

FEATURES:

- Max reading: 1999 counts
- Rated Voltage: 100V, 250V, 500V, 1000V
- Insulation Resistance Range : 1MΩ ~ 20GΩ
- Dielectric Absorption Ratio Test (DAR)
- Polarization Index Test (PI)
- Low Battery Indication
- Overload Indication: LCD displays "OL"
- Operation Environment: Temperature: 0°C - 40°C; Humidity:30% -80% RH
- Storage Environment: Temperature: -10°C - 50°C; Humidity <85%RH
- Powered Supply: a) 6 X 1.5V AA Size batteries.
b) External Power Supply
- Display: 80 x 60mm.
- Dimension: 173 x 123 x 60 mm½
- Weight: 500g including Batteries
- Accessories: Instructional manual, Carrying Pouch, 6 Nos. 1.5V AA Batteries, Test Leads.



SPECIFICATION:

Voltage	Measurement Range	Accuracy
100V	1MΩ~500MΩ	±8%
250V ~ 500V	1MΩ~10GΩ	±8%
1000V	1MΩ~20GΩ	±10%
Voltage Test Range : 30 ~ 750V AC		Accuracy : ±2%