

## VIDEO BOROSCOPE BS150

**APPLICATION:** The BS-150 detects internal parts of machinery that are otherwise inaccessible, making it possible to inspect whether equipment is operating normally (e.g., cars and heavy machinery). It features a gooseneck camera that can be placed underwater to inspect submerged objects, ideal for drainage pipeline work. It is suitable for use in special monitoring environments, such as inspections underneath vehicles. It can also be used for outdoor and wild adventure safety inspections. It complies with European CE safety standards.

### FEATURES:

- On-site inspection by photos and videos
- Image rotation by pressing UP & DOWN buttons under video mode
- Images display with the current time and date
- Single image or video deletion
- Image and video recording
- Display with time and date
- SD Card (32GB)
- Flash Card (8GB)
- Built-in 65M Flash Capacity
- TV-OUT
- Video Format (MP4 AVI, 3GP, ASF)
- Image Photo Format (JPG.JPEG)
- Languages: English, French, German, Spanish, Turkish
- Support operation in a dark environment (with four LED lights)
- USB 2.0 connection to the computer
- IP 67 - Water and Dust Proof data



### SPECIFICATION:

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>➤ Display Size: 3.2 inch</li> <li>➤ TFT Display Pixel 240 (RGB) *320</li> <li>➤ Photosensitive Devices 1/4 inch CMOS</li> <li>➤ Sensor Pixel 640*480</li> <li>➤ Photo Resolution 640*480</li> <li>➤ Maximum Number of Frames (FPS) 30FPS/S</li> <li>➤ Colour Digit(bit) 24</li> <li>➤ Focusing Distance Fixed at 5-1Scm</li> <li>➤ Gooseneck Length 1m (2m/3m selectable)</li> <li>➤ Camera Diameter 17mm</li> <li>➤ Video Format MPEG4/3GP/AVVASF</li> <li>➤ Photo Format JPEG</li> <li>➤ Camera Video Format 3GP</li> </ul> | <ul style="list-style-type: none"> <li>➤ Saved Image Format JPG (640*480)</li> <li>➤ SD Card MAX 32GB</li> <li>➤ Flash Memory MAX 8GB</li> <li>➤ Working Voltage Li battery 3.7V/2000mA</li> <li>➤ Video Working Current Approx. 380mA</li> <li>➤ Static Current MAX 20μA</li> <li>➤ TV OUT PAL / NTSC system</li> <li>➤ Operating Temperature 0°C--50°C</li> <li>➤ Charging Temperature -20°C--60°C</li> <li>➤ Storage Temperature -20°C--60°C</li> <li>➤ Storage Humidity 15% to 85%RH</li> <li>➤ Data Output USB data cable and SD card</li> <li>➤ Power Supply 3.7V,2000mA'h battery (1860)</li> <li>➤ Size(L,W,H) 240mm*100mm*160mm</li> </ul> |
|--|---|

**ACCESSORIES:** User manual, 3.7V lithium battery, package box.